






GRILLE PANEL



GRILLE PANEL (Europe)



Features

- High efficacy up to 125lm/w.
- 5 years warranty.
- IP20 IK04



Application

Factory, office building, shopping center, home lighting etc.



GRILLE PANEL (Europe)

Product Parameter

Model	XL-PLE22XX-AZZ-G	XL-PLE14XX-AZZ-G
Color Temp(K)	3000-3500-4000K	
UGR	1:UGR<16	
SIZE	595X595X32.5mm	595X1195X32.5mm
Wattage (W)	36W	48W
Efficacy(lm/w)	>125LM/W	
CRI	>80	
Voltage	220-240V	
PF	>0.9	
Beam angle	85°	
Working Temperature	-25℃ -45℃	
Relative Humidity	10%-90%RH	
Gross weight	/kg	
Carton size	648X255X618mm 6PCS/CTN	1248X255X318mm 6PCS/CTN

Model Instructions

Company Code	Category	Area	Dover	IP	UGR	Colors adjustable	CCT	Version
XL	PL	E	30	IP	X	X	ZZ	X
	PL= Panel Light	E= Europe	30=30W 40=40W	1 2	U=UGR<19; N=NO UGR Request	S=single color A= Adjustable	30=3000K 35=3500K	G



GRILLE PANEL (Europe)

Photometrics

